

Analogue Single Zone Module **CHQ-SZM2(SCI)**



Features

- ▶ Loop powered
- ▶ Up to 6 Conventional Detectors
- ▶ Single loop address
- ▶ Remote LED output
- ▶ Fully monitored for short and open circuit faults
- ▶ DIN rail version available
- ▶ Both models feature an integral short-circuit isolator
- ▶ Both models approved by LPCB & VdS

Description

Model CHQ-SZM2(SCI) is a Single Zone Monitor designed to allow up to 6 conventional detectors to be interfaced to Hochiki's ESP analogue addressable system. The unit is also available as a DIN Rail mountable version; with or without an integral short-circuit isolator. The CHQ-SZM2(SCI) utilises simple DIL switches for reliable addressing. A back box is also available (CHQ-BACKBOX) which, when used in conjunction with the CHQ-SZM(SCI), increases the IP rating to IP65. **The conventional zone on the CHQ-SZM2(SCI) does not support any line continuity options; if Call Points are being interfaced they should be wired at the beginning of the zone.**

Specification		
Order codes	CHQ-SZM2(SCI) (module with SCI) CHQ-SZM2/DIN(SCI) (DIN module with SCI)	
Operating voltage	17 - 41 V dc	
Quiescent current	260 μ A	
Current consumption	22 mA \pm 20 % (polling)	
Current in short-circuit	8 mA	
Maximum short-circuit current	1 A	
E.O.L device	TE-RH-E (polarity conscious)	
Zone voltage	15.3 V - 17.1 V	
Zone resistance	50 Ω (Max)	
Zone capacitance	0.3 μ F (Max)	
Detectors per zone	DCA, DFB, DFE – No limit. SLG, SLK, SLR, SIF, SIH, SIJ, DCC, DCD, DFJ – 6 max. SPB-ET, SPC-ET or SRA-ET– Only one and no other detectors. HF-24 – only one and no other detectors, DRD-E – 3 max, CCP-E – No limit	
Operating Temperature Range	-10 °C to +50 °C	
Storage Temperature Range	-30 °C to +60 °C	
Maximum Humidity	95%RH Non Condensing (at 40 °C)	
Weights (g) & Dimensions (mm)	CHQ-SZM2(SCI) 328	L=157 x W=127 x D=35 (module inc lid) D=79 (module inc lid & CHQ-BACKBOX) (add 235 to module weight when using CHQ-BACKBOX)
	CHQ-SZM2/DIN(SCI) 114	L=119 x W=108 x D=24
Colour & enclosure material	CHQ Module & CHQ-BACKBOX White ABS, DIN Module Green ABS, Module Lid Semi-Opaque Black ABS as standard (white version – CHQ-LID(WHT) also available)	

Fire alarm control panel compatibility required for these products.

For more information on these products, please contact:



T: 00353 47 86274 / 00353 47 86663

E: Sales@irishsafetysystems.ie