

Context Plus

NC802DB

Standard Call Point Button Reset c/w Remote Socket



Overview

An attractively designed button-operated call/reset point capable of generating Standard calls on an 800 Series Call System.

Includes a 6.35mm jack plug socket for the connection of an optional tail call lead, pressure mat or other ancillary calling device.

Red reassurance LED confirms a call has been made.

Onboard reset button cancels calls made from the NC802DB and standard calls made from other devices wired on the same zone (such as ceiling pull units in Ensuite areas).

Mounts on a standard UK 25mm single gang flush or surface back box.

NC802DM

Standard Call Point Magnetic Reset c/w Remote Socket



Overview

An attractively designed button-operated call point capable of generating Standard calls on an 800 Series Call System.

Includes a magnetic reset 'target' that requires a separately-available NC803M magnetic reset key to operate.

Red reassurance LED confirms a call has been made.

Includes a 6.35mm jack plug socket for the connection of an optional tail call lead, pressure mat or other ancillary calling device.

Onboard magnetic reset 'target' cancels calls made from the NC802DM and standard calls made from other devices wired on the same zone (such as ceiling pull units in Ensuite areas).

Mounts on a standard UK 25mm single gang flush or surface back box.

NC804DE

Emergency Only Call Point Button Reset



Overview

A button-operated call/resetpoint capable of generating Emergency calls on an 800 Series Call System.

Onboard reset button cancels Emergency calls made from the NC804DE and Standard calls made from other devices wired on the same zone (such as ceiling pull units in Ensuite areas).

Ideal for use as a reset point for ceiling pull units that will allow a more urgent Emergency call to be made if additional assistance is required.

Red reassurance LED confirms a call has been made.

Mounts on a standard UK 25mm single gang flush or surface back box.

NC802DEWM

Water Resistant Alert Point IP65 Magnetic Reset



Overview

A surface-mounting IP65 rated water-resistant alert point capable of generating Standard or Emergency calls on an 800 Series Call System.

Comprises a light grey back box, yellow lid and bright red push button.

Ideal for use alongside swimming pools and other 'wet' areas.

Red reassurance LED confirms a call has been made.

Includes an onboard magnetic reset facility (requires an NC803M magnetic reset key, not supplied). Alternatively wire to a separate 800 Series reset point.

Supplied with two stickers, one reading 'Call for Assistance' and one reading 'Push for EMERGENCY'.

Slave water-resistant alert points (NC802DEWS) also available.

NC302RXC

Master Infrared Ceiling Receiver



Overview

A ceiling-mountable infrared receiver that will accept Standard & Emergency calls from compatible 800 Series infrared transmitters.

Can receive line-of-sight infrared signals from around 10m away (dependent on physical conditions and environmental factors).

Red reassurance LED confirms a call has been made.

Can be connected to up to three NC302RXCS slave infrared ceiling receivers to increase coverage in long corridors, large rooms, etc.

Requires a separate remote reset point such as our NC802DB button reset, NC800DM magnetic reset or NC800IRR keyswitch reset points for cancelling calls.

Mounts on a standard UK 25mm single gang flush or surface back box.

NC302RXCS

Slave Infrared Ceiling Receiver



Overview

A ceiling-mountable slave infrared receiver specifically designed to extend the coverage of 800 Series master infrared receivers.

Max. three NC302RXCS slave infrared ceiling receivers per NC302RXC master ceiling receiver or NC802DERB/DERM infrared call point.

Will accept Standard & Emergency calls from compatible 800 Series infrared transmitters.

Can receive line-of-sight infrared signals from around 10m away (dependent on physical conditions and environmental factors).

Mounts on a standard UK 25mm single gang flush or surface back box.

For more information on these products, please contact us:



T: 00353 47 86274 / 00353 47 86663

E: Sales@irishsafety.com