



**QT606**  
Slave Overdoor Light



**Overview**

Provides visual indication of calls made from a Quantec call point outside bedrooms, WCs, etc.

Flash and colour sequence changes/intensifies to reflect the urgency of the incoming call.

Dual red and green LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Finished in tough, durable ABS plastic.

## QT606A

Addressable Overdoor Light c/w Sounder



### Overview

An addressable overdoor light & sounder designed to increase call indication levels in large Quantec sites.

Can be programmed to illuminate and sound when certain groups of call points are calling.

Ideal for providing area indication or 'follow me' lights at the ends of corridors, etc

Flash and sound rates change/intensify to reflect the urgency of incoming calls.

Adjustable volume control.

Dual red and green LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Finished in tough, durable ABS plastic.

## **QT688**

Addressable Sounder



### **Overview**

An addressable sounder designed to increase call indication levels in large Quantec sites.

Can be programmed to sound when certain groups of call points are calling.

Sound rate changes/intensifies to reflect the urgency of incoming calls.

Adjustable volume control.

Connections for an optional slave overdoor light.

Mounts on a standard UK 25mm single gang flush or surface back box.

Finished in tough, durable ABS plastic.

## QT688/2

Hi-Output Addressable Sounder



### Overview

A programmable hi-output addressable sounder operating at up to 85dB(A).

Designed to increase call indication levels in large Quantec sites.

Can be configured to sound when certain groups of call points are calling.

Can be assigned one of 16 different tones (four of which are HTM2015 compliant) for each of Quantec's call states using aQT423 configurator.

Default operation utilises Quantec's standard tones.

Adjustable day/night volume controls.

Connections for an optional slave overdoor light.

Mounts on a standard UK 25mm single gang flush or surface back box.

For more information on these products, please contact us:



T: 00353 47 86274 / 00353 47 86663

E: Sales@irishsafetysystems.ie