

## CIRCU-Lite

Circular 28W 2D IP65 rated luminaire with white base and opal diffuser

The Circu-Lite offers both mains and emergency lighting in a simple but stylish luminaire with a white polycarbonate base and opal polycarbonate diffuser, sealed to IP65.

### Installation

The Circu-Lite is supplied with a unique lever release for the diffuser which provides access to the control gear and lamp, which are mounted on a removable gear tray. The luminaires are available with mains only or switchable maintained operation. Non-maintained can be achieved by excluding the normal switched mains supply.

### Operation

All emergency versions provide 3 hour duration as standard, from integral high temperature Nickel Cadmium batteries. Maintained versions can be used for standard switched mains lighting but will automatically provide emergency lighting in the event of a complete loss of normal mains supply. Dali dimming controls can be added as an option.

The Circu-Lite fully complies to the requirements of EN60598.2.22. It also fully supports all the features of the Lux Intelligent range of emergency lighting test panels.



### Key Features

- Decorative circular luminaire
- Standard and dimmable versions available
- Fully compatible with Lux Intelligent
- Fully complies with all aspects of EN60598.2.22

### Specification

Supply Voltage	230 Volts (220-240V) @ 50Hz
Light Source	28W 2D
Supply Current	Maintained:160mA Non-maintained:40mA
Battery	4.8V 4Ahr
Recharge Period	24 Hours (14 hours 1 hour duration)
Cable Entry	20mm side entry, 13mm hole in rear
IP Rating	IP65 Ta 25°C
Dimensions (mm)	330 (Diameter) x 126 (Height)

### Order Codes and Options

UL28/M3/P:	Circu-Lite 28W 3 hour maintained addressable luminaire
UL28/AC:	Circu-Lite 28W mains only luminaire
UL28/M3/P/Dali:	Circu-Lite 28W 3 hour maintained addressable luminaire with dali operation
UL28/AC/Dali:	Circu-Lite 28W mains only luminaire with dali operation

For more information on these products, please contact us: